TECHNICAL DATA SHEET

1.3″



20186 LED 180° PL HYBRID

TWO PIN-BASE REPLACEMENT LAMPS FOR CFLS

PRODUCT DETAILS

ELECTRICAL	
Wattage	4.5W
Voltage	120-277V
Current	40mA
Power Factor	N/A
Total Harmonic Distortion (THD)	N/A
LIGHTING PERFORMANCE	
Lumens	450
Lumens Per Watt (Lm/W)	100
Color Temperature (CCT)	5000K
Color Rendering (CRI)	83
Beam Angle	180°
Light Distribution	N/A
Dimmable Lighting Control	DUT CHARACLE
ENVIRONMENT	
Operating Temperature	-20°C ~ 45°C
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Style	Enclosed
CERTIFICATIONS	

50,000 5 N/A Aluminum / PC G23 2 Pin / Plug In White	
N/A Aluminum / PC G23 2 Pin / Plug In	
Aluminum / PC G23 2 Pin / Plug In	
Aluminum / PC G23 2 Pin / Plug In	
G23 2 Pin / Plug In	
G23 2 Pin / Plug In	
•	
White	
White	
20pc / 10899645001759	
899645001752	
China	
9405.40.8200	
6.5"(L) x 1.3"(W) x 0.8"(H)	
──────────────────────────────────────	

- DIRECT WIRE OR PLUG & GO[™] - Simple rewiring installation allows lamps to run on

Replaces CFL PL Lamps with G23/2 Pin base frequently used in downlights and

the main or use it with a magnetic ballast as a plug and go.

ORDERING

RoHS compliant

ITEM#	DESCRIPTION	CASE
20186	LED 4.5WPL/180°/FR/50K/G23/2 PIN/120-277V HYBRID	20

II

FEATURES

Exceptional efficacy.

APPLICATION

sconces.

Universal voltage using direct wire.