


# LED

## Plug-and-Play U-Bend T8 LED Tube



### FEATURES

- Suitable replacement for 32-Watt T8 and 34 or 40-Watt T12 U-bend fluorescent tubes
- Operates with an existing electronic ballast
- Can be used with shunted and non-shunted sockets with compatible ballasts
- Has a Bi-Pin G13 base
- DLC® Part Number: PLTSP19115

### TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Leg Spacing	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90024	6 in.	2200	15W	5000K	Plug-and-Play	82	YES	Medium Bi-Pin	5 Year

### SPECIFICATIONS

BULB SHAPE .....	T8	COATING .....	N/A
DIMMABLE .....	NO	FLUORESCENT EQUAL .....	32-WATT
SAFETY RATING .....	UL DAMP	COMPATIBILITY .....	ELECTRONIC BALLASTS
COLOR .....	DAYLIGHT WHITE	LAMPHOLDER(S) .....	SHUNTED & NON-SHUNTED
LIFE HOURS .....	50,000	LENS .....	FROSTED GLASS
SYSTEM WATTAGE .....	17.5W	LENGTH .....	22.425 IN.
VOLTAGE .....	120-277	DIAMETER .....	1.1 IN.