



**75W**  
REPLACEMENT

**90+**  
CRI

**10W**  
Watts

E26

**120V**  
Voltage

DAMP  
LOCATION

Dimmable

High quality of light and color rendering (90+ CRI, 50+ R9),  
with low flicker, flicker <30%,  
Smooth dimming. Dimming lower than 10%.





## ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.013	750LM	10W	2700K	40°	>90	>0.9	≥1315cd
SE-350.014	750LM	10W	3000K	40°	>90	>0.9	≥1315cd

## MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.013	3.74in X 4.53in	5.11oz	-20°C - 40°C	12pcs	48pcs
SE-350.014	3.74in X 4.53in	5.11oz	-20°C - 40°C	12pcs	48pcs






## RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

## R VALUES

R1=92	R2=97	R3=99	R4=91	R5=92	R6=97	R7=90
R8=79	R9=55	R10=92	R11=93	R12=85	R13=94	R14=100



## TM30 GRAPHIC

TM-30 deals with the color rendition of object.

Rf- a fidelity index that is similar to the commonly used CRI

Rg- a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

