



100W
REPLACEMENT

60W
REPLACEMENT

30W
REPLACEMENT

90+
CRI

17W
Watts

E26d

120V
Voltage

DAMP
LOCATION

3-WAY

High quality of light and color rendering (90+ CRI, 50+ R9),
3-way dimming.

Can adjust from 1600lm to 800lm to 450lm..






ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.093	1600LM/800LM/450LM	17W	2700K	270°	>90	>0.7	-
SE-350.149	1600LM/800LM/450LM	17W	3000K	270°	>90	>0.7	-

MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.093	2.76in X 5.28in	4.7oz	-20°C - 40°C	12pcs	48pcs
SE-350.149	2.76in X 5.28in	4.7oz	-20°C - 40°C	12pcs	48pcs





RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES

R1=95	R2=99	R3=98	R4=94	R5=95	R6=97	R7=91
R8=83	R9=66	R10=97	R11=95	R12=84	R13=97	R14=100

