



**100W**  
REPLACEMENT

**90+**  
CRI

**17W**  
Watts

**GU24**

**120V**  
Voltage

**DAMP LOCATION**

**Dimmable**

High quality of light and color rendering (90+ CRI, 50+ R9),

with low flicker, flicker <30%,

Smooth dimming. Dimming lower than 10%.





## ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.091	1600LM	17W	2700K	270°	>90	>0.9	-
SE-350.092	1600LM	17W	3000K	270°	>90	>0.9	-

## MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.091	2.76in X 5.0in	5.17oz	-20°C - 40°C	12pcs	48pcs
SE-350.092	2.76in X 5.0in	5.17oz	-20°C - 40°C	12pcs	48pcs






## RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.



## TM30 GRAPHIC

TM-30 deals with the color rendition of object.

$R_f$ - a fidelity index that is similar to the commonly used CRI

$R_g$ - a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

