



60W
REPLACEMENT

- 90+**
CRI
- 10W**
Watts
- E26**
- 120V**
Voltage
- DAMP LOCATION**
- Dimmable**

High quality of light and color rendering (90+ CRI, 50+ R9),
Smooth dimming. Dimming lower than 20%.






ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-350.049	800LM	10W	2700K	270°	>90	>0.7	-
SE-350.050	800LM	10W	3000K	270°	>90	>0.7	-

MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-350.049	2.40in X 4.43in	1.94oz	-20°C - 40°C	12pcs	48pcs
SE-350.050	2.40in X 4.43in	1.94oz	-20°C - 40°C	12pcs	48pcs






RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES

R1=93	R2=98	R3=97	R4=91	R5=93	R6=97	R7=90
R8=79	R9=57	R10=95	R11=93	R12=86	R13=95	R14=99



TM30 GRAPHIC

TM-30 deals with the color rendition of object.

R_f- a fidelity index that is similar to the commonly used CRI

R_g- a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

