

LED

2 ft. Plug-and-Play T8 Tube



FEATURES

- DLC® Part Number: PLTSP48115
- Suitable replacement for 32-Watt fluorescent T8 and T12 tubes
- Operates with an existing electronic ballast
- Compatible with shunted lampholders
- UL listed for damp locations
- Bi-Pin G13 base

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90006	2 ft.	1250	10W	5000K	Plug-and-Play	80	YES	Medium Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T8	LIFE HOURS	50,000
DIMMABLE	NO	FLUORESCENT EQUAL	17-WATT
SAFETY RATING	UL DAMP	COMPATIBILITY	ELECTRONIC BALLASTS
COLOR	Daylight White	LAMPHOLDER(S)	SHUNTED
LIFE HOURS	50,000	LENS	FROSTED GLASS
LUMENS PER WATT	120	LENGTH	23.67 IN.
VOLTAGE	120-277	DIAMETER	0.98 IN.